



## High Pressure Compressed Air Dryer

Our static and mobile Desiccant Dryers offer cutting edge technology working to  $-70^{\circ}\text{C}$  PDP (Pressure dew point) at 25barg, thus providing market leading control over the level of moisture within your process.

Digital control panels enable you to change dryer pressures instantly, across a range of pressures from 0.3millibars to 49barg, making GenAir desiccant dryers the most versatile in the market.



Technical Data	
Max. working Pressure	25barg (365psi)
Max. free air delivery	56m <sup>3</sup> /min (1989cfm)
Pressure dew point	$-40^{\circ}\text{C}$ ( $-70^{\circ}\text{C}$ on request)
Type	Heatless Desiccant
Max. inlet temperature	Up to $32^{\circ}\text{C}$
Filtration	Down to 0,01 $\mu$
Length	2840mm
Width	1880mm
Height	2120mm
Weight	8200kg

All of our equipment is fully maintained by our team of specialist compressor engineers and supported with the provision of a full range of ancillaries and complimentary products including dryers, generators, lighting towers and bowsers.

Unit 28 & 29 Prothero Works  
Bilport Lane, Wednesbury  
West Midlands, WS10 0NT

Tel: 0844 775 0890  
Email: [sales@genair.co.uk](mailto:sales@genair.co.uk)

To experience GenAir for yourself please call 0844 775 0890 or visit us at [www.genair.co.uk](http://www.genair.co.uk) to discuss your needs.

National coverage from our depots in Wednesbury and Slough.